



# Z-Select 4000D 3.2mil Receipt

## FEATURES

- Direct thermal, smooth, uncoated, paper receipt
- Excellent print quality
- 25 year archivability\*
- Available in 3.2mil (65774RM)

## MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White smooth coated direct thermal paper	3.2 mil
TOTAL ± 10%		3.2 mil

## TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
NA	-40°F to 140°F (-40°C to 60°C)	72° F (22° C) at 50% RH

### Expected Exterior Life

Not recommended for outdoor use

## CHEMICAL RESISTANCE

	Chemical	Direct Thermal
Weak	Blood	●
	Body Fluid	●
	Salt Water	●
	Water	●
	Window Cleaner	●
Moderate	Alcohol	NR
	Ammonia	NR
	Bleach	NR
	IPA	NR
Harsh	Gasoline	NR
	Grease	NR
	Oil	NR
Extreme	Acetone	NR
	IR Reflow	NR
	MEK	NR
	TCE	NR
	Xylene	NR

● Recommended ● Test in Your Application NR Not Recommended

## SUGGESTED APPLICATIONS

- Packing lists



- General purpose ticketing



- Work in process tagging



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit [www.zebra.com/supplies](http://www.zebra.com/supplies)

**Product Performance and Suitability:** The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | [inquiry4@zebra.com](mailto:inquiry4@zebra.com)

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.



**ZEBRA**

# Z-Select 4000D 3.2mil Receipt

## Recommended Tone Settings for Zebra printers using Speed 3, Contrast 0:

	MZ220, MZ320, QL220Plus, QL320Plus, QL420Plus, QLn220, QLn320, QLn420, RW420, RW220, ZQ320, ZQ310	iMZ320, ZQ510, ZQ520
Z-Perform 1000D 2.4mil Receipt	0	20

\*Images will remain legible for up to 25 years provided they are formed properly and the receipts are handled and stored under the proper conditions. For archival use these receipts need to be protected from exposure to light, heat, water, solvents, cleaners, plasticizers, and oils (including vegetable oils and skin oils), and they need to be stored with compatible materials at temperatures less than 77°F, and 45-65% RH. Image durability depends on the energy used to print the receipts. To maximize image durability, receipts should be printed at the recommended tone settings.

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

**For more information, visit [www.zebra.com/supplies](http://www.zebra.com/supplies)**

**Product Performance and Suitability:** The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | [inquiry4@zebra.com](mailto:inquiry4@zebra.com)

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.